

PRODUCT PERSPECTIVE: EXTENDERS

PS/2 KVM EXTENDERS



VGA PS/2 KVM Extender via CAT5 up to 91 Meters

The XTENDEX® ST-C5KVM-300 KVM Extender provides local and remote KVM (PS/2 keyboard, PS/2 mouse and VGA monitor) access to a PC or NTI KVM switch up to 91 meters using CAT5/5e/6 UTP cable. They consist of two units, the local unit and the remote unit, which are interconnected with CAT5/5e/6 cable. The extender is available with optional stereo audio, and supports 1280x1024 video resolution at 91 meters; higher resolutions are supported at shorter distances up to 1920x1440. Complies with CE and RoHS standards. Two-year warranty.



VGA PS/2 KVM Extender via CAT5 up to 183 Meters

The XTENDEX® KVM extender provides local and remote KVM (PS/2 keyboard, PS/2 mouse and VGA monitor) access to a PC or NTI KVM switch up to 183 meters using CAT5/5e/6 UTP cable. The ST-C5KVM-600 is available with optional stereo audio or RS232 control, and supports 1024x768 video resolution at 183 meters; higher resolutions are supported at shorter distances up to 1920x1440. The extender is available with optional stereo audio, and supports 1280x1024 video resolution at 91 meters; higher resolutions are supported at shorter distances up to 1920x1440. Complies with CE, FCC, and RoHS standards. Two-year warranty.



Hi-Res VGA PS/2 KVM Extender via CAT5 up to 305 Meters

The XTENDEX® ST-C5KVM-1000S KVM extender provides local and remote KVM (PS/2 keyboard, PS/2 mouse and VGA monitor) access to a PC up to 305 meters using CAT5/5e/6 UTP cable. It consists of two units, the local unit and remote unit, which are interconnected with CAT5/5e/6 cable. The extender is available with optional two-way audio, RS232, or two-way audio + RS232. Supports resolutions to 2048x1536. Complies with CE and RoHS standards. Two-year warranty.

USB KVM EXTENDERS



VGA USB KVM Extender via CAT5 up to 91 Meters

The XTENDEX® ST-C5USBV-300 USB KVM extender provides local and remote KVM (USB keyboard, USB mouse and VGA monitor) access to a USB computer up to 91 meters via CAT5/5e/6 cable. The extender is available with optional stereo audio. Supports resolutions to 1920x1440. Complies with CE and RoHS standards. Two-year warranty.



VGA USB KVM Extender via CAT5 up to 305 Meters

The XTENDEX® ST-C5USBV USB KVM extender provides local and remote KVM (USB keyboard, USB mouse and VGA monitor) access to a USB computer up to 305 meters using CAT5/5e/6 cable. Supports resolutions to 1920x1440. It consists of two units, the local unit and remote unit, which are interconnected with CAT5/5e/6 cable. Complies with CE and RoHS standards. Two-year warranty.

VGA EXTENDERS



VGA Extender via CAT5 up to 91 Meters

The XTENDEX® ST-C5V-300 VGA Extender transmits VGA video up to 91 meters away from a computer using CAT5/5e/6 cable. The extender supports local and remote monitors, and is available with optional stereo audio. It supports resolutions to 1920x1440. Complies with CE and RoHS standards. Two-year warranty.



VGA Extender via CAT5 up to 183 Meters

The XTENDEX® ST-C5V-600S VGA Extender transmits VGA video up to 183 meters away from a computer using CAT5/5e/6 cable. The extender supports local and remote monitors, and is available with optional stereo audio or RS232 control. It supports resolutions to 1920x1440. Complies with CE, FCC and RoHS standards. Two-year warranty.



Hi-Res VGA Extender via CAT5 up to 305 Meters

The XTENDEX® ST-C5V-1000S VGA Extender transmits VGA video up to 305 meters away from a computer using CAT5/5e/6 cable. The extender supports local and remote monitors, and is available with optional two-way audio, RS232 or two-way audio + RS232. It supports resolutions to 2048x1536. Complies with CE and RoHS standards. Two-year warranty.

DVI EXTENDERS



DVI Extender via CAT5e/6 up to 91 Meters

The XTENDEX® ST-C5HDMI-300 DVI Extender transmits digital DVI video up to 91 meters away from a DVI source using two CAT5e/6 cables. Each video extender consists of a local unit that connects to a DVI source and a remote unit that connects to a DVI display. It supports computer resolutions to 1920x1200, and HDTV resolutions to 1080i. Complies with CE, FCC, and RoHS standards. Two-year warranty.



DVI Extender via Fiber Optic Cable up to 1,509 Meters

The XTENDEX® DVI Extender via Fiber Optic Cable locates a single link digital DVI display up to 1,509 meters away from a computer using fiber optic cable. Each extender consists of a transmitter that connects to a computer and a receiver that connects to a monitor. Four models are available; each model supports a different resolution up to 1,509 meters: ST-FODVI-LC-1024 supports up to 1024x768; ST-FODVI-LC-1280 supports up to 1280x1024; ST-FODVI-LC-1600 supports up to 1600x1200; ST-FODVI-LC-1920 supports up to 1920x1200. Complies with CE, FCC and RoHS standards. Two-year warranty.



DVI-D Fiber Cables and Long DVI-D Copper Cables up to 100 Meters

The DVI-FO-xx-MM DVI-D Fiber Optical Extension Cable locates a single link digital DVI display up to 100 meters from a computer with no loss of signal - delivering crystal clear digital images instantly. The cables are an integrated DVI-D cable solution, which includes the fiber optics components and the DDC signals built into the cable and the DVI connectors. It supports up to 1920x1440 resolution.

The DVI-D XTENDEX® DVI-DS-xx-MM Copper Extension Cable extends a DVI-D display up to 30 meters from a video source. It supports resolutions to 1900x1200. Complies with FCC, CE and RoHS standards. Two-year warranty.

HDTV EXTENDERS



Component Video + Stereo Audio Extender

The XTENDEX® ST-C5HDTV-600 HDTV + Stereo Audio Extender transmits YPbPr component video and analog audio up to 183 meters away from a component video device using CAT5/5e/6 cable. The extender supports local and remote displays and speakers, and resolutions up to 1080p. Complies with CE, FCC and RoHS standards. Two-year warranty.



Component Video + Digital Audio Extender

The XTENDEX® ST-C5HDA-600 HDTV + Digital Audio Extender transmits YPbPr component video and digital audio up to 183 meters away from a component video device using CAT5/5e/6 cable. The extender supports local and remote displays and speakers, and resolutions up to 1080p. Complies with CE, FCC and RoHS standards. Two-year warranty.



HDMI Fiber Cables for High-Resolution Long Runs to 100 Meters

The XTENDEX® HDMI-FO-xx-FF HDMI Fiber Optical Extension Cable transmits HDMI video up to 100 meters using an integrated cable solution, which includes fiber optic components and DDC signals built into the cable and connectors. It supports resolutions up to 1080p. Complies with FCC, CE and RoHS standards. Two-year warranty.



HDMI/DVI Extender via CAT5e/6 up to 91 Meters

The XTENDEX® HDMI Extender transmits digital video and audio signals up to 91 meters using two CAT5e/6 cables. Each video extender consists of a local unit that connects to an HDMI source and a remote unit that connects to an HDMI display. Supports HDTV resolutions to 1080i and computer resolutions to 1920x1200. Complies with FCC, CE and RoHS standards. Two-year warranty.

HDTV EXTENDERS (Continued)



HDMI Extender via Fiber Optic Cable up to 1,524 Meters (5,000 Feet)

The XTENDEX® ST-FOHDMI-LC HDMI Extender via Fiber Optic Cable locates a digital HDMI display up to 1,524 meters (5,000 feet) away from a video source using fiber optic cable. Each extender consists of a transmitter that connects to a video source and a receiver that connects to a display. Two-year warranty.

S-VIDEO EXTENDERS



S-Video Extender via CAT5 up to 183 Meters

The XTENDEX® ST-C5SV-600 S-Video Extender transmits S-Video up to 183 meters away from an S-Video device using CAT5/5e/6 cable. The extender supports local and remote monitors, and is available with optional stereo audio. It supports 800x600 S-Video resolution. Complies with CE, FCC and RoHS standards. Two-year warranty.

RACKMOUNT EXTENDERS



Multiple Extender Modules in a Rack: USB PS/2 VGA KVM

The XTENDEX® Rackmount Extender Module Tray allows you to mount up to 12 extender modules in a space-saving 2RU shelf. The local and remote extender modules are interconnected via CAT5/5e/6 cable. Available extender modules: USB KVM extender to 91 meters with optional audio; PS2 KVM extender to 183 meters with optional audio or RS232; and VGA extender to 183 meters with optional audio or RS232. Optional power distribution module powers up to 12 Rackmount Extender Modules. Complies with CE and RoHS standards. Two-year warranty.

USB & FIREWIRE EXTENDERS



USB Extender via CAT5 up to 46 Meters

The USB-C5-LC extends one USB device up to 46 meters, and the USB-C5(-CE) extends four USB devices up to 30 meters. The USB extenders consist of two units, the local unit and the remote unit, which are interconnected with CAT5/5e/6 cable. Complies with FCC, CE, and RoHS standards. Two-year warranty.



Firewire Extender via Fiber Optic Cable up to 1,000 Meters (3,280 Feet)

The XTENDEX® Firewire Optical Extender extends a firewire device up to 1,000 meters (3,280 feet) using multimode fiber optic cable. The Firewire extender consists of two units, the local unit and the remote unit, which are interconnected with multimode fiber optic cable. Complies with CE, FCC, and RoHS standards. Two-year warranty.



Firewire Extender via CAT5e/6 up to 76 Meters

The XTENDEX® ST-C51394-250 extends one FireWire device up to 76 meters using CAT6 cable and 46 meters using CAT5e cable. The Firewire extender consists of two units, the local unit and the remote unit, which are interconnected with CAT5/5e/6 cable. Complies with CE, FCC, and RoHS standards. Two-year warranty.